

Fitting & Care Instructions

Installation

Remove or retract your antenna. See below if you have a fixed antenna.

Pull your cover over the roof of your vehicle from the back to the front. Drop your cover over the sides, then fit the elastic hem of your cover under the front bumper of your vehicle. Secure your cover under the rear bumper and corners.

To secure your cover on your vehicle, attach one end of the supplied rope to a web loop set in the side of your cover. Toss the rope under the vehicle and tie the rope to the web loops on the opposite side. For extra security you may also use a cable lock in these web loops (cable lock not supplied).



Antennas

Check your antenna - many antennas simply unscrew at their base. If your antenna cannot be removed or retracted, you will need to make a small hole in your cover for it.

Put your cover on as much of your vehicle as you can without covering the antenna. Mark the area where your cover will go over the antenna. With a sharp pencil or pen, carefully push a small hole in your cover. Peel the backing from your antenna patch (Fig. 1, supplied) and, centering the hole in the patch over the hole in your cover, adhere the patch to the outside of your cover. Press the patch down firmly. Carefully lift your cover down over your antenna, threading your antenna through the hole, and finish fitting your cover.

Care

Clean your cover with a soft brush and lukewarm water or machine wash in **COLD** water. **DO NOT USE SOAP** as it may remove the protective coating added by the factory. Line dry only; do not machine dry.

Avoid trapping moisture under your cover. If your vehicle is outside for long periods or under snow, trapped moisture can sometimes cause paint to become cloudy.

We recommend removing your cover every 30 days. Let your vehicle dry completely before reinstalling you cover.

Storage

A convenient storage bag is provided for your cover. Be sure the cover is completely dry before you store it in the storage bag for an extended period.

Two Year Limited Warranty

This product is factory warranted for workmanship and materials for 2 years from the date of purchase.

Made by
Classic Accessories, Inc., Kent WA 98032